

ProTour®

Asymmetric Courts Lights

PADEL
NEDERLAND
ALUMINIUM PADELDANEN

5
years
warranty



High Efficiency High Quality

It is designed to be cost-saving for project requirements. Most importantly, the price is very competitive with 150Lm/W high efficiency.


Multi-beamangle Lighting Distrubition

15°/ 30°/ 60°/ 90°/ 120°/ T2M/ T3M.
All kinds of different beam-angle better for different project, such as tennis courts, basketball courts, volleyball, etc

Useful light

Adopting polarized light design with minimized light pollution and light loss.

Tunnel lighting design and light distribution




IP66 & IK08

Optic structure adopts PC lens and tempered glass with IK08 and IP66 protection rating.

Vent

Balance atmosphere pressure and prevent moisture.

Outdoor billboard lighting design and light distribution



Different Watt Different Dimensions



Dimensions

	10W	20W
Luminaire Net Weight	0.6Kg	1.1Kg
Outlook Dimensions	182*122*47mm	242*168*51mm
Carton Size	395*270*290mm	510*365*315mm

	30W	50W
Luminaire Net Weight	1.6Kg	2.7Kg
Outlook Dimensions	282*220*52mm	337*269*52mm
Carton Size	465*305*315mm	588*360*315mm


	100W	150W
Luminaire Net Weight	4.0Kg	4.5Kg
Outlook Dimensions	394*394*56mm	445*392*56mm
Carton Size	440*420*115mm	490*420*115mm

	200W	300W
Luminaire Net Weight	5.5Kg	8.7Kg
Outlook Dimensions	497*392*56mm	503*545*64mm
Carton Size	540*420*115mm	580*550*115mm

ProTour® 150Lm/w

Model No.-No.Dim	LA-PROT10-MW	LA-PROT20-MW	LA-PROT30-MW	LA-PROT50-MW	LA-PROT100-MW	LA-PROT150-MW	LA-PROT200-MW	LA-PROT300-MW	LA-PROT320-MW
Lumen Output	1,500lm	3,000lm	4,500lm	7,500lm	15,000lm	22,500lm	30,000lm	45,000lm	48,000lm
Wattage	10W	20W	30W	50W	100W	150W	200W	300W	320W
Luminous Efficiency	150lm/W								
Smart Control	Constant Lumen output / Timer / Daylight sensor / Dali dimming / 0-10V Dimming								
CCT	3000-6500K								
IP Rating	IP66								
IK Rating	IK08								
Working Temperature	-20 ~ +45°C								
LED Chips	PHILIPS								
LED Driver	Meanwell								
Input Voltage	100-270Vac, 50/60Hz, ≥0.90								
Warranty	5 years								
Lifespan	>50,000hrs								
Beamangle	15°/ 30°/ 60°/ 90°/ 120°/ T2M/ T3M								
CRI	Ra>80								
Net Weight/Carton	12.0Kg	22.0Kg	15.0Kg	26.0Kg	3.8Kg	4.8Kg	5.7Kg	8.7Kg	8.7Kg
Gross Weight/Carton	14.0Kg	24.0Kg	17.0Kg	28.0Kg	4.4Kg	5.1Kg	6.1Kg	9.3Kg	9.3Kg
Quantity/Carton	20pcs	20pcs	10pcs	10pcs	1pcs	1pcs	1pcs	1pcs	1pcs
Carton Size	395*270*290mm	510*365*315mm	465*305*315mm	588*360*315mm	440*420*115mm	490*420*115mm	540*420*115mm	580*550*115mm	580*550*115mm

Light Distribution Optional



Intelligent Control

- ▶ DALI Control
- ▶ 1-10V Dimming
- ▶ Motion Sensor

Certifications

